


PRACTICAL OPERATION & MAINTENANCE (O&M) MANUAL ON SOLAR PV SYSTEMS

**FOR RURAL CLINICS (CHPS COMPOUNDS) IN
KWAHU AFRAM PLAINS DISTRICT, GHANA**

**Prepared by: Ing. Marina D.K. Agortimevor
Technical Advisor
GIZ Green People's Energy Project**

April 2023



Contents

Introduction	3
Solar Photovoltaic (PV) Systems	3
Description Of Installed System at CHPS Compounds	3
Operations	4
Start Up Procedure.....	4
Shut Down Procedure	6
Emergency Shut Down Procedure.....	6
Inverter Operation & Display Panel.....	7
Energy Efficiency & Loads to Use.....	8
ALLOWED AC LOADS	8
<u>DISALLOWED AC LOADS</u>	8
Maintenance	9
Common Tools & Equipment Used.....	9
Maintenance Warnings.....	9
Maintenance Tips	10
System Failure	11
Periodic Maintenance Schedule	11


Introduction

Solar Photovoltaic (PV) Systems

A solar photovoltaic (PV) system is composed of **one or more solar panels combined with an inverter and other electrical and mechanical hardware that use energy from the Sun to generate electricity**. PV systems can vary greatly in size from small rooftop or portable systems to massive utility-scale generation plants

A typical photovoltaic system consists of some or all of the following components:

- Solar Panel - Converts sunlight to electricity/DC power
- Inverter - Converts DC power from the solar panel and battery to AC power.
- Battery(s) - Stores excess electricity generated by solar panel



Description Of Installed System at CHPS Compounds


A 2KWP STANDALONE PV SYTEM

The system is a standalone system which is a system independent of the electricity grid, with the excess energy produced being stored in batteries to be used and managed by an inverter. The size of the PV system installed is 2000Wp.

The PV module used is a polycrystalline cell type specifically Ameri AS- 6P 340W. The inverter used is a TBB Apollo Maxx which is a multi-functional inverter, combining functions of inverter, solar charger and battery charger to offer uninterruptible power support in a portable size. The battery used is a Ritar DG 12V200Ah battery. 12 batteries are installed.

An AC distribution board (ACDB) (also known as panel board, breaker panel, or electric panel) is present. The primary function of the ACDB is to serve as a control point to regulate all AC power to connected loads. It houses miniature circuit breakers to disconnect incoming and outgoing AC connections.

The images below show one of the installed systems at a CHPS compound and its components:



Operations

Start Up Procedure

WARNING: You must follow the shutdown procedure in the order of the steps stated. Failure to follow the sequence can result in arcing and damage to the system. A fire is possible. Also, make sure all loads are off before you begin.

Note: Next to the inverter is a start-up procedure label similar to this.

Figure 1



STEP 1: Turn **ON** the circuit breaker in the “DC/ ENERGY BOX” tagged “BATTERY”, See **figure 1**. The box sits in between the battery and the inverter for protection and isolation functions

STEP 3: Switch **ON** the solar panels by turning **ON** the circuit breaker in the “DC/ ENERGY BOX” tagged “SOLAR PANEL”, See **figure 1**. Wait until the inverter recognises the PV panels. A PV panel symbol will appear on the information screen of the inverter; See **figure 3** below

STEP 5: Within the “AC/ENERGY BOX”, switch **ON** the breaker tagged “LOAD” or “MAIN”, (see **figures 4 & 5**) to connect the output energy to the Distribution Box

Figure 2



ON/OFF button

STEP 2: If the inverter does not start automatically, locate the **ON/OFF** button underneath the inverter (see **figure 2**) and press and hold for 2 seconds to put it into standby mode. The power LED will light up and the LCD will enter into the self-diagnostic mode.

STEP 4: Wait on standby mode for 30 seconds, then press the **ON/OFF** button (see **figure 2**) again for 1 second to turn on the inverter into the inverting mode. Then observe the LCD and inverter LED to make sure the inverter is running normally.

Figure 3





Figure 4



Figure 5




Shut Down Procedure

WARNING: You must follow the shutdown procedure in the order of the steps stated. Failure to follow the sequence can result in arcing and damage to the system.

Note: Next to the inverter is a shutdown procedure label similar to this. After the inverter is powered OFF, there is still residual power and heat in the chassis, which may lead to electric shock or burning. Therefore, after the inverter is powered off, wait for 5 minutes if you will be opening the chassis of the inverter.

See shutdown procedure below:



Emergency Shut Down Procedure



In the case of an emergency like fire, smoke etc, immediately turn off all breakers in this order:



Then follow up with the rest of the shut down procedure stated above.

Inverter Operation & Display Panel

The operation and display panel includes four buttons and an LCD display, indicating the operating status and input/output power information. See images below:



Button	Function
ESC	To exit the setting mode or confirm the fault code
UP	To go to the previous selection.
DOWN	To go to the next selection.
ENTER	To enter the setting mode or confirm the selection

LED Indicator			Function
Invert	Green	Solid on	Inverter mode
		Flashing	Power Assist mode
Charge	Green	Solid on	The battery is charging
		Flashing	The battery is fully charged
Fault	Red	Solid on	Fault occurs
		Flashing	Warning occurs

Energy Efficiency & Loads to Use


ALLOWED AC LOADS



LED Light Bulbs



Charging of Mobile Phones & Lamps



Ceiling Fan/Standing Fan



Television



Vaccine Refrigerator



Laptop



Portable Ultrasound Machine

Note:

1. Use more of the loads during sun hours(8am-5pm) to reduce discharge of the batteries at night. Eg. Charging of phones, lamps etc should be done in the daytime.
2. Check power rating of electrical appliances before you connect to the solar system. Total power rating of electrical loads of the facility should not exceed 1900W to prevent system shutdown.

DISALLOWED AC LOADS



Electric Kettle



Pressing Iron



Electric Immersion Boiler



Hair Dryer

Maintenance

Common Tools Used



Multi Meter



Screw Drivers



Spanners



Hammers



Pliers



Maintenance Warnings

WARNING: Do not attempt to clean or come in contact with the surface of a solar module with broken glass. This could result in a dangerous electric shock.

WARNING: Solar modules remain live during daylight hours, even when the DC isolator is off. Therefore, wiring etc. will still be energised even when the DC isolators are off. Hazardous voltages are present whenever solar panels are exposed to light.


WARNING: The system should be shut down following the shutdown procedure before performing any maintenance.

WARNING: Read and obey all warning signs before performing any maintenance




CAUTION: Appropriate precautions must be taken when working at heights. Do not attempt to access the roof unless the precautions to prevent falling from heights are in place. GIZ recommends that only GHS focal persons/certified electrician who have been trained to work at heights conduct all solar system maintenance at height.

Maintenance Tips

1. Clean solar panel with soft cloth or soft mop and water anytime it is dirty. Do this when panels are cool and do not use soap/detergent for cleaning. Also do not step on the solar panel nor use pressure washers for cleaning.



2. Trim trees that may create shade over the panels.
3. Clean inverter, DC and AC (Energy) box, and batteries when dusty with a dry soft cloth or soft hand dusting brush.



4. Do not put anything on top of the batteries, keep it free and dry from any liquid especially water.
5. Battery terminals must be covered



6. Do not touch the battery terminals with metal objects; otherwise, you can get an electric shock.
7. Check connections for loose contact/connections and tighten them.



System Failure

If the system appears to be not functioning, i.e. blank LCD and no LED lights:

1. Please verify that all breakers are in the “on” position.
2. If the screen remains blank, switch all breakers off by the shut-down procedure stated earlier. Leave inverter in the “off” position for 10 minutes then re-energise by the start-up procedure.
3. If the inverter is still not functioning, please put the Leave inverter in the “off” position and contact the technical focal person at GHS or the supplier company DENG Ltd..

Periodic Maintenance Schedule

SUB-SYSTEM OR COMPONENT	MAINTENANCE ACTION	FREQUENCY	REMARKS	RESPONSIBLE
SITE	Verify: <ol style="list-style-type: none"> 1. General Cleanliness (accumulation of debris around and/or under array/ batteries and environment). Follow tips above. 2. Check impact of bats on the roof and PV system 3. Check shading of solar panels from surrounding trees. In case of shading, cut parts of tree that are causing shadow. 	Weekly	Clean if necessary	In - Charges/volunteers
PV MODULES	<ol style="list-style-type: none"> 1. Verify Cleanliness (accumulation of dust or fungus on array) 2. Cleaning: Simply wash with water to remove layers of dust and dirt. Follow tips above. 	monthly	Clean if necessary	In- Charges/volunteers
	<ol style="list-style-type: none"> 1. Visual check of connectors and cables 2. Check roof for cracks and holes and repair where necessary 3. Clearing of obstructions of sunlight/shading to the panels (trees etc.) 	Quarterly	Repair/ tighten if necessary Trim trees if required.	In- Charges/volunteers

	Check for visual defects including: <ol style="list-style-type: none"> 1. Fractures 2. Cracks and Chips 3. Browning 4. Moisture Penetration 5. Frame Corrosion 	Biannually	Modules with visual defects should be further inspected for performance and safety to determine the need for replacement.	Technical focal persons
	Verify Bypass Diodes	Annually	Any defective seals, clamps and bypass diodes are to be replaced	Technical focal persons
	Verify Mechanical Integrity of Conduits	Quarterly	Any damaged conduit is to be replaced	Technical focal persons
	Verify Insulation Integrity of Cables installed without conduit	Quarterly	Any damaged cables to be replaced	Technical focal persons
WIRING INSTALLATION	Check Junction & Distribution Boxes for: <ol style="list-style-type: none"> 1. Tightness of Connections 2. Water accumulation/build up 3. Integrity of Lid Seals 	Annually	Any defective seals, clamps, blocking diodes and surge arresters are to be replaced.	Technical focal persons
	<ol style="list-style-type: none"> 4. Integrity of Cable Entrance and/or Conduit sealing 5. Integrity of Clamping devices 			
ELECTRICAL CHARACTERISTIC	Measure Open Circuit Voltages	Annually		Technical focal persons
	Measure Short Circuit Currents	Annually		

<p style="text-align: center;">PROTECTIVE DEVICES</p>	<p>Verify:</p> <ol style="list-style-type: none"> 1. Integrity of Fuses 2. Operation of Circuit breakers and RCD's (perform short circuit tests) 3. Operation of Solar Array Isolation Devices 4. Operation of earth fault protection system <p>Earthing Check for:</p> <ol style="list-style-type: none"> 1. Tightness of Connections 2. Corrosion 3. Solar Panels earthing condition 4. Inverter earthing condition 5. Solar farm earthing condition <p>Conducting an earth resistance test and confirming that value is within accepted limits.</p>	<p style="text-align: center;">Annually</p>	<p style="text-align: center;">Correct and improve earthing if necessary</p>	<p style="text-align: center;">Technical focal persons</p>
<p style="text-align: center;">BATTERIES</p>	<p>Check:</p> <ol style="list-style-type: none"> 1. For carbons on the battery terminals. If found, grease the terminals 2. Voltages of the various batteries for their threshold <p>Ensure long term record keeping of battery state of charge (soc)</p>	<p style="text-align: center;">Quarterly</p>		<p style="text-align: center;">Technical focal persons</p>
<p style="text-align: center;">INVERTER</p>	<ol style="list-style-type: none"> 1. Visual inspection, external cleaning and blowing of dust from vents and fan areas Use dry cloth to wipe away dust 2. Verify that LEDs are working properly and wiring is intact. 	<p style="text-align: center;">Quarterly</p>		<p style="text-align: center;">Technical focal persons</p>
<p style="text-align: center;">MOUNTING STRUCTURES</p>	<p>Visual check of stability, rigidity, fixing and tightening of the mounting rails, bolts and clamps on panels as well as other fastening devices to verify their integrity.</p> <p>Inspection for Corrosion</p>	<p style="text-align: center;">Quarterly</p> <p style="text-align: center;">Biannually</p>		<p style="text-align: center;">Technical focal persons</p>